

**1161 0073 0****1161 0034 0****1161 0065 0**

***Quality Vinyl Sheet  
You can trust!***

**1161 0074 0****1161 0004 0****1161 0016 0****1161 0053 0****1161 0018 0****1161 0033 0**



Technical Parameters			
Warranty period (years)	10		
Surface protection	Polyurethane PUR		
Usability class	PN-EN 649+PN-EN 685	34/43	
EC-Certificate of Conformity	PN-EN 14041	1488-CPD-0017/W	
Reaction to fire	PN-EN 13501-1	B <sub>f1</sub> -s1	
Hygiene attest	-	Pass	
Electrical properties	PN-EN 14041	Astatic and conducting	
Electrical resistance	PN-EN 1081	≤ 10 <sup>9</sup> OHM	
Electrostatic voltage	PN-EN 1815	≤ 2kV	
Slip resistance	PN-EN 14041	Class DS	
Dynamic friction factor	PN-EN 13893	0,36 / 0,41	
Total thickness	PN-EN 428	mm	2,0
Thickness of wear layer	PN-EN 429	mm	2,0
Weight	PN-EN 430	kg/m <sup>2</sup>	3,0
Roll width	PN-EN 426	m	2
Roll length	PN-EN 426	m	20
Wear resistance	PN-EN 660-2	-	Group T
Residual indentation	PN-EN 433	mm	≤ 0,1
Dimensional stability after exposure to heat	PN-EN 434	%	≤ 0,4
Curling after exposure to heat	PN-EN 434	mm	≤ 8
Light resistance	PN-ISO 105-B02	-	> 7
Flexibility	PN-EN 435	-	Good
Chemical resistance	PN-EN 423	-	Good
Resistance to microorganisms	PN-EN ISO 846	-	Yes
Resistance to impact of wheeled chair	PN-EN 425	-	Good
Possibility to install in rooms with floor heating	Yes		